


JIS B2401 (旧JIS W1516) O型圈 AN6227番 规格表
 (用于运动、圆筒面固定)
 (航空器用O型圈油压用)



JIS 编号称呼	AS 568 编号称呼	O型圈尺寸	
		线径d2	内径d1
1	006	1.78±0.07	2.9
2	007		3.68
3	008		4.47
4	009		5.28
5	010		6.07
6	011		7.65
7	012		9.25
8	110		9.19
9	111	2.62±0.07	10.77
10	112		12.37
11	113		13.94
12	114		15.54
13	115		17.12
14	116		18.72
15	210		18.64
16	211		20.22
17	212	21.82	
18	213	23.39	
19	214	24.99	
20	215	26.57	
21	216	3.53±0.10	28.17
22	217		29.74
23	218		31.34
24	219		32.92
25	220		34.52
26	221		36.09
27	222		37.69
28	325		37.46
29	326	40.64	
30	327	43.82	
31	328	46.99	
32	329	50.16	
33	330	53.34	
34	331	56.52	
35	332	59.69	
36	333	5.33±0.12	62.86
37	334		66.04
38	335		69.22
39	336		72.39
40	337		75.56
41	338		78.74
42	339		81.92
43	340		85.09
44	341	88.26	
45	342	91.44	

JIS 编号称呼	AS 568 编号称呼	O型圈尺寸	
		线径d2	内径d1
46	343	5.33±0.12	94.62
47	344		97.79
48	345		100.96
49	346		104.14
50	347		107.32
51	348		110.49
52	349		113.66
53	426		116.84
54	427	6.98±0.15	120.02
55	428		123.19
56	429		126.36
57	430		129.54
58	431		132.72
59	432		135.89
60	433		139.06
61	434		142.24
62	435	145.42	
63	436	148.59	
64	437	151.76	
65	438	158.12	
66	439	164.46	
67	440	170.82	
68	441	177.16	
69	442	6.98±0.15	183.52
70	443		189.86
71	444		196.22
72	445		202.56
73	446		215.26
74	447		227.96
75	448		240.66
76	449		253.36
77	450	266.06	
78	451	5.33±0.12	278.76
79	452		291.46
80	453		304.16
81	454		316.86
82	455		329.56
83	456		342.26
84	457		354.96
85	458		367.66
86	459	380.36	
87	460	393.06	
88	425	113.66	±0.38