

AURUM工程塑料紧固件 热可塑性聚酰胺(Polyelamide)

● 该材料为非结晶性工程塑料。其最大的特点是洁净性, 与其他超级工程塑料相比, 在高温下气体的释放量少, 用于半导体等要求洁净性很高的领域. 耐热性及耐腐蚀性也好, 被广泛用于办公自动化设备的零部件, 电气-电子零部件, 汽车ATF零部件等领域。

● 连续使用温度0℃ ● 燃烧性UL94 V-0

图片	名称 (编号)	规格				
	盘头螺丝 (AURUM/PH)	M3	M4	M5	M6	M8
	节距	0.5	0.7	0.8	1	1.25
	长度					
	6	○	○			
	8	○	○	○		
	10	○	○	○		
	12	○	○	○		
	15	○	○	○	○	○
	20	○	○	○	○	○
	25			○	○	○
	30			○	○	○
	35				○	○
40					○	
	内六角 螺丝 (AURUM/CB)	M3	M4	M5	M6	M8
	节距	0.5	0.7	0.8	1	1.25
	长度					
	6	○	○			
	8	○	○			
	10	○	○	○	○	○
	12	○	○	○		
	15	○	○	○	○	○
	20	○	○	○	○	○
	25	○	○	○	○	○
	30			○	○	○
	35			○	○	○
40				○	○	
	六角 螺母 (AURUM/NT)	M3	M4	M5	M6	M8
节距	0.5	0.7	0.8	1	1.25	
	垫片 (AURUM/W)	3	4	5	6	8
d x D	3.2x7	4.3x9	5.3x10	6.4x12.5	8.4x17	
厚度t	0.5	0.8	1	1.6	1.6	