

PC工程塑料紧固件 聚碳酸酯(Polycarbonate)

●该材料为非结晶性工程塑料。具有超群的抗冲击强度、机械性能和电特性综合优异，被广泛用于电气、电子、医疗、汽车等领域。

●连续使用温度115℃ ●燃烧性UL94 V-2

	内六角定位螺丝 (PC/HS)	M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度										
	4					○					
	5				○						
	6				○	○					
	8				○	○					
10				○	○						
	外六角螺丝 (PC/BT)	M4	M5	M6	M8	M10	M12				
	节距	0.7	0.8	1	1.25	1.5	1.75				
	长度										
	10	○	○	○	○	○					
	12	○	○	○	○	○					
	15	○	○	○	○	○	○				
	20	○	○	○	○	○	○				
	25	○	○	○	○	○	○				
	30		○	○	○	○	○				
	35		○	○	○	○	○				
	40			○	○	○	○				
	45						○				
	50				○	○	○				
60						○					
70						○					
	内六角螺丝 (PC/CB)	M3	M4	M5	M6	M8					
	节距	0.5	0.7	0.8	1	1.25					
	长度										
	6	○	○								
	8	○	○								
	10	○	○	○	○	○					
	12	○	○	○							
	15	○	○	○	○	○					
	20	○	○	○	○	○					
	25	○	○	○	○	○					
30			○	○	○						
35			○	○	○						
40				○	○						
	六角螺母 (PC/NT)	M2	M2.6	M3	M4	M5	M6	M8	M10	M12	W3/8
	节距	0.4	0.45	0.5	0.7	0.8	1	1.25	1.5	1.75	1.5875
	垫片 (PC/W)	2	2.6	3		4	5	6	8	10	12
	d x D	2.1x4	2.7x6	3.3x8	3.3x10	4.5x10	5.5x12	6.5x13	8.5x18	10.5x22	13x24
	厚度t	0.5	0.5	0.8	0.8	0.8	0.8	1	1.6	1.6	2.5
	垫片 (PC/SW)					4	5	6			
	d x D					3.65x10	4.6x12	5.5x13			
	厚度t					0.8	0.8	1			