



## PTFE工程塑料紧固件 聚四氟乙烯(Polytetrafluoroethene)

●该材料也称之为特氟隆，是氟树脂中的代表材料。对几乎所有的化学品、溶剂具有化学惰性，而求具有优异的电/机特性、不粘性及润滑性，被最广泛应用于化学、机电、宇宙开发等领域。

●连续使用温度260℃ ●燃烧性UL94 V-0

图片	名称 (编号)	规格						
		M3	M4	M5	M6	M8	M10	M12
	六角螺丝 (PTFE/BT)	M3	M4	M5	M6	M8	M10	M12
	节距	0.5	0.7	0.8	1	1.25	1.5	1.75
	长度							
	6	○						
	8	○	○					
	10	○	○	○				
	12	○	○	○				
	16	○	○	○	○			
	20	○	○	○	○	○		○
	25		○	○	○	○	○	○
	30			○	○	○	○	○
	40				○	○	○	○
	50					○	○	○
	60						○	○
70							○	
	六角螺母 (PTFE/NT)	M3	M4	M5	M6	M8	M10	M12
	节距	0.5	0.7	0.8	1	1.25	1.5	1.75
	垫片 (PTFE/W)	3	4	5	6	8	10	12
	d x D	3.2x7	4.3x9	5.3x10	6.4x12.5	8.4x17	10.5x21	13x24
	厚度t	0.5	0.8	1	1.6	1.6	2	2.5