





PVDF工程塑料紧固件 聚偏氟乙烯(polyvinylidene fluoride)

●PVDF树脂兼具氟树脂和通用树脂的特性，除具有良好的耐化学腐蚀性、耐高温性、耐氧化性、耐候性、耐射线辐射性能外，还具有压电性、介电性、热电性等特殊性能。

●连续使用温度85℃ ●燃烧性UL94 V-0

图片	名称 (编号)	规格									
		M1.7	M2	M2.6	M3	M4	M5	M6	M8	M10	M12
	六角螺丝 (PVDF/BT)	M1.7	M2	M2.6	M3	M4	M5	M6	M8	M10	M12
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25	1.5	1.75
	长度										
	10						○	○			
	12						○	○			
	15						○	○	○		
	20						○	○	○		
	25						○	○	○		
	30										
35											
40						○	○	○			
	内六角 螺丝 (PEEK/FH)	M1.7	M2	M2.6	M3	M4	M5	M6	M8	M10	M12
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25	1.5	1.75
	长度										
	5				○	○					
	6				○	○					
	8				○	○					
	10				○	○	○	○	○		
	12				○	○	○	○	○		
	15				○	○	○	○	○	○	
	20					○	○	○	○	○	○
	25						○	○	○	○	○
	30						○	○	○	○	○
35						○	○	○	○	○	
40							○	○	○	○	
	六角 螺母 (PP/NT)						M5	M6	M8	M10	M12
	节距						0.8	1	1.25	1.5	1.75
	垫片 (PP/W)						5	6	8	10	12
	d x D						5.3x10	6.4x12.5	8.4x17	10.5x21	13x24
	厚度t						1	1.6	1.6	2	2.5